SUNPOWER

BENEFITS

Highest Efficiency

Panel efficiency of 18.4% is higher than any commercially available competitor panel.

More Power

SunPower 300 delivers 50% more power per unit area than conventional solar panels and 100% more than thin film solar panels.

Reduces Installation Cost

More power per panel means fewer panels per install. This saves both time and money.

Reliable and Robust Design

Proven materials, tempered front glass, and a sturdy anodized frame allow panel to operate reliably in multiple mounting configurations.



300 SOLAR PANEL

EXCEPTIONAL EFFICIENCY AND PERFORMANCE



The SunPower 300 Solar Panel provides today's highest efficiency and performance. Utilizing 96 next generation SunPower all back-contact solar cells, the SunPower 300 delivers an unprecedented total panel conversion efficiency of 18.4%. The 300 panel's reduced voltagetemperature coefficient and exceptional low-light performance attributes provide outstanding energy delivery per peak power watt.

SunPower's High Efficiency Advantage - Up to Twice the Power

Comparable systems covering 1000 m ² / 10,750 ft ²				
	Thin Film	Conventional	SunPower	
Watts / Panel	65	165	300	
Efficiency	9.0%	12.0%	18.4%	
kWs	90	120	184	



SPR-300-WHT-I

SUNPOWER

300 SOLAR PANEL

EXCEPTIONAL EFFICIENCY AND PERFORMANCE

Electrical Data Measured at Standard Test Conditions (STC): irradiance of 1000/m², air mass 1.5 g, and cell temperature 25° C				
Peak Power (+/–3%)	Pmax	300 W		
Rated Voltage	Vmp	54.7 V		
Rated Current	Imp	5.49 A		
Open Circuit Voltage	Voc	64.0 V		
Short Circuit Current	lsc	5.87 A		
Maximum System Voltage	IEC	1000 V		
Temperature Coefficients				
	Power	–0.38% / °C		
	Voltage (Voc)	–176.6 mV/°C		
	Current (Isc)	3.5 mA/°C		
Series Fuse Rating		15 A		
Peak Power per Unit Area		184 W/m ²		

Mechanical Data



Current/voltage characteristics with dependence on irradiance and module temperature.

Tested Operating Conditions		
Temperature	-40° C to +85° C (-40° F to +185° F)	
Max load	240 kg/m² (2400 Pascals) front and back	
Impact Resistance	Hail – 25mm (1 in) at 23 m/s (52 mph)	

Solar Cells	96 SunPower all back-contact monocrystalline	Impact
Front Glass	4.0 mm (5/32 in) tempered	
Junction Box	IP-65 rated with 3 bypass diodes	
Output Cables	900 mm length cables / Multi-Contact connectors	Warran
Frame	Anodized aluminum alloy type 6063	
Weight	24 kg, 53 lbs	Certifico

Warranty and Certifications		
Warranty	25 year limited power warranty	
	10 year limited product warranty	
Certifications	IEC 61215, Safety tested IEC 61730	



CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT. Go to www.sunpowercorp.com/panels for details

About SunPower

> SunPower designs, manufactures and delivers high-performance solar electric technology worldwide. Our high-efficiency solar cells generate up to 50 percent more power than conventional solar cells. Our high-performance solar panels, roof tiles and trackers deliver significantly more energy than competing systems.

© April 2008 SunPower Corporation. All rights reserved. Specifications included in this datasheet are subject to change without notice.